

8105

Product



KRAMER
on the safe side



The intelligent performance wheel loader

The Kramer wheel loader 8105 is part of the premium 8 series and is equipped with the tested Kramer system of the one-piece chassis. The machine impresses with high-performance parameters, reliability and comfort with simultaneous receipt of optimal manoeuvrability and excellent stability. The unique high-performance engine of 100 HP is optionally available and turns the 8105 into a real high-performance loader. The perfectly located operator's cab in combination with the extensive glazing enable optimal all-round visibility.

- Propulsive force: Maximum propulsive forces and best traction through efficient high-pressure drive systems and 100% differential lock
- Safety: The wide entries and exits on both sides enable safe entering and exiting of the cabin
- 24-inch tyres: The optional 24 inch tyres enable perfect traction, excellent quiet running and optimal lift capacity
- Maximum flexibility: The three steering modes: front-wheel, all-wheel and crab steering are available as series standard
- Panoramic cab: The large cab (2.3 m³) with entry on both sides, as well as glazing of large areas enables

excellent all-round visibility

8105 Technical specifications

Operating data		
Bucket capacity (standard bucket)		1.05 m ³
Operating weight		5,550 kg
Engine / Motor		
Engine / Motor manufacturer		Deutz
Engine performance (standard)		55.4 kW
Engine performance (option)		74 kW
Emission standards stage		V
Emission standards stage (standard)		V
Power transmission		
Traction drive	Continuously variable, hydrostatic axial piston transmission	
Travel speed (standard)		20 km/h
Travel speed (option)		30 km/h
Driving speed (option)		40 km/h
Standard tires		14.5-20
Differential lock		100% connectable
Max. steering angle		2x40 °
Steering and operating hydraulics		
Max. pump discharge capacity		84 l/min
Max. pump pressure		240 bar
Max. Powerflow discharge capacity		120 l/min
Kinematics		
Design system	Parallel kinematics	
Tipping load (with bucket)		4,100 kg
Payload (S=1.25)		2,500 kg
Tilt-in angle		50 °
Tip-out angle		42 °
Filling capacities		
Fuel tank		120 l
Hydraulic oil tank		64 l
DEF tank (Deutz 3.6)		10 l
Sound emission		
Measured value		100 dB(A)
Guaranteed value		101 dB(A)
Noise level at the driver's ear		77 dB(A)
Vibrations		
Total vibrations value of the upper body extremities		< 8.2 feet/s ²
Highest effective value of weighted acceleration for the body		< 1.64 feet/s ²

All statements without guarantee.

Additional technical data is available in the detailed brochure in the informational material section

8105 Dimensions

A	Height	2,640 mm
B	Length	5,710 mm
C	Width	1,920 mm
D	Ground clearance	350 mm
E	Wheelbase	2,150 mm
	Center of front axle to tip of teeth	1,940 mm
F	Center of rear axle to end of vehicle	1,620 mm
G	Bucket width	2,050 mm
H	Bucket pivot point	3,259 mm
I	Overhead loading height	3,050 mm
J	Dumping height	2,500 mm
K	Dump reach	750 mm
	Stack height	3,000 mm
	Turning radius (over tyres)	2,950 mm

Alle Angaben wurden mit folgender Bereifung ermittelt: 28 x 9.00 - 15

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.
Copyright © 2020 Kramer-Werke GmbH.