



5065T

Telescopic wheel loader

The compact telescopic wheel loader.

The Kramer 5065T is equipped with the Kramer quick hitch system and the telescopic loading system allows for more reach and stacking height. Due to the undivided frame and all-wheel steering, the constant payload and stability are fully available with this telescopic wheel loader. With a stacking height of up to 4.0 m, the model is also ideal for loading vehicles.

Safety: The back tilt angle limitation of 45° at maximum lift height protects the operator and machine from unintentional material loss.

Cost Reduction: The efficient high-pressure traction drive ensures low operating costs and high thrust.

Loading system: The optimal design of the loading system ensures the best visibility of the attachments and the quick-change plate.

Compact dimensions: The low overall height of less than 2.5 m and the narrow vehicle width of less than 1.65 m enable easy and cost-effective transport of the telescopic wheel loader.

Unbeatable maneuverability: The realization of a turning radius of only 2,900 mm (outer edge of tire) through 2 x 38° steering angle.

Technical Data

Exhaust after-treatment	DOC / DPF	Lift capacity (max.)	32.5 kN
Engine manufacturer	Yanmar	Tank capacity for fuel	60 l
Drive output	34.3 kW	Tank capacity for hydraulic oil	58 l
Displacement	2,190 cm ³	Travel speed Standard	0-20 km/h
Drive output	46 PS	Travel speed Option 1	0-30 km/h
Bucket content (standard bucket)	0.65 m ³	Work hydraulics discharge volume (max.)	56 l/min
Operating weight	3,500 - 4,600 kg	Work hydraulics working pressure (max.)	240 bar
Tipping load (standard bucket)	2,500 kg	Kinematics type	Z
Tipping load (pallet fork)	2,060 kg	Steering angle max.	38 Grad
Payload (S=1.25)	1,650 kg		

Dimensions

A1	Total length	5,350 mm
B1	Wheel base center	2,000 mm
D5	Height with cab	2,470 mm
H1	Load-over height / retracted	3,160 mm
H2	Load-over height / extended	4,010 mm
I1	Dumping height / retracted	2,650 mm
I2	Dumping height / extended	3,500 mm
J1	Dumping width / retracted	560 mm
J2	Dumping width / extended	810 mm
L1	Total width	1,595 mm
M1	Ground clearance	280 mm
O1	Steering angle	38 °
P1	Swing angle	8 °
Y1	Bucket width	1,650 mm
Z1	Stacking height / retracted	3,180 mm
Z2	Stacking height / extended	4,030 mm